

TAPE PRINTER

PRODUCT NUMBER 2795.14.001

Printer



- › Dot matrix printer
- › Paper width up to 76 mm
- › Endless label paper
- › With tearing edge

TAPE PRINTER

PRODUCT NUMBER 2795.14.001



Features

General description

- > 9-pin printer with full graphic capability with print speed of 3.1 lines per second
- > Semi-automatic "drop-in and insert" paper feed
- > Small space requirement with compartment for external power adapter under the printer
- > ESC/POS-compatible
- > Ivory colour housing
- > MCBF 18 million lines (acc. to Weibull)

- > Paper winder and interface cartridge replaceable by user.
- > Sensor to signal "paper low"
- > With tear-off edge

Typical applications

- > Voucher printer: with paper winder
- > Log printer: data recording, metrology, journal

Technical data

Detail	Description	Detail	Description
Print method	Dot-matrix printer, 9 needles	No. of copies	Original + 2 copies (max. 0.2mm)
Print direction	bidirectional	Emulation	Star mode or ESC/POS mode
Print speed	approx. 3.1ch/s (42 characters, 16.9cpi)	Ink tape	RC700BR: 2 colours (black/red)
Paper feed	approx. 23ch/s	Interface	serial RS 232 C
Characters per line	40/42/35	Print memory	4KB or 256KB
Character matrix	7 x 9 or 5 x 9	Reliability	5 million lines (MCBF), 18 million lines (acc. to Weibull)
Character size	wxh 1.2 x 2.42mm/wxh 1.5 x 2.42mm	Approvals	VCCI Class A, FCC Class A, UL, C-UL, TÜV, CE, GS
Print density	16.9cpi/14.1cpi	Power supply	100-240V ~ 1,4 A 50/60 Hz
Character set	95 alphanum., 32 internat., 128 x 8 graphics	Options	Paper winder (PW2000), Windows and OPOS drivers
Code pages	38 code pages	Dimensions	160 x 173.3 x 252.5
Paper width	76 ± 0,5mm; 57,5 ± 0,5mm; 69,5 ± 0,5mm	Weight	3kg, without paper
Roll diameter	max. 85mm		
Thickness	0,06-0,085 mm (single copy)		

Ordering information

Order Number	Description
2795.14.001	Tape printer

Your Soehnle Professional dealer:

www.soehnle-professional.com