




# Compact scale Basic

9120/9121/9122

- ▶ Fast and easy single-key operation with extra-large key
- ▶ Terminal can be pulled out by up to 30 mm
- ▶ Large LC display (no backlighting), character height: 20 mm
- ▶ Energy-efficient due to integrated Auto-off function
- ▶ Internal user calibration for location-specific adjustments



## Features

---

- ▶ High-resolution single-range scale, not approvable
- ▶ Fast and easy single-key operation with extra-large key
- ▶ Rechargeable battery operation and extra low-profile design facilitate flexible use in different locations
- ▶ Terminal can be pulled out by up to 30 mm. Benefits: Bigger weighing surface without obstructing the terminal, better access to plug-in connections
- ▶ Internal user calibration for location-specific adjustments
- ▶ Weight units switchable between kg and lb
- ▶ Functions: Weighing, taring, adding, plus / minus / check, hold, removal weighing
- ▶ Large LC display (no backlighting), character height: 20 mm
- ▶ Weighing platform: Stainless steel 1.4301
- ▶ Base frame: Powder-coated steel or stainless steel 1.4301 (only protection class IP 65)
- ▶ Terminal housing: Plastic
- ▶ Integrated rechargeable battery with plug-in power supply 100 – 240 V / 50 – 60 Hz, Operating time: 50 hours, charging time: 5.5 hours, UK power adapter see options
- ▶ Energy-efficient due to integrated Auto-off function of the rechargeable battery with adjustable timer from 1 – 30 minutes or continuous operation
- ▶ Scale dimensions / scale weight:
  - ▶ 310 x 355 x 70 mm, 6 kg
  - ▶ 400 x 380 x 75 mm, 10 kg
  - ▶ 520 x 480 x 75 mm, 20 kg (powder-coated)
  - ▶ 520 x 480 x 100 mm, 23 kg (stainless steel)
- ▶ Protection class IP 42 or IP 65
- ▶ Scale leveling up to 10 mm with 4 adjustable feet and spirit level
- ▶ Nominal operating temperature: -10°C to 40°C



## Products

Order number Variation	Approvable	Division g	Maximum load kg	Model substructure	Platform size mm	Protection class
9120.01.040 Compact scale Basic	No	0.1	3	Powder coated	310 x 275	IP 42
9120.02.040 Compact scale Basic	No	0.2	6	Powder coated	310 x 275	IP 42
9120.03.040 Compact scale Basic	No	0.5	15	Powder coated	310 x 275	IP 42
9120.04.040 Compact scale Basic	No	1	32	Powder coated	310 x 275	IP 42
9121.02.040 Compact scale Basic	No	0.2	6	Powder coated	400 x 300	IP 42
9121.03.040 Compact scale Basic	No	0.5	15	Powder coated	400 x 300	IP 42
9121.04.040 Compact scale Basic	No	1	32	Powder coated	400 x 300	IP 42
9121.05.040 Compact scale Basic	No	2	60	Powder coated	400 x 300	IP 42
9122.04.040 Compact scale Basic	No	1	32	Powder coated	520 x 400	IP 42
9122.05.040 Compact scale Basic	No	2	60	Powder coated	520 x 400	IP 42
9120.01.140 Compact scale Basic	No	0.1	3	Powder coated	310 x 275	IP 65
9120.02.140 Compact scale Basic	No	0.2	6	Powder coated	310 x 275	IP 65
9120.03.140 Compact scale Basic	No	0.5	15	Powder coated	310 x 275	IP 65
9120.04.140 Compact scale Basic	No	1	32	Powder coated	310 x 275	IP 65
9120.11.140 Compact scale Basic	No	0.1	3	Stainless steel	310 x 275	IP 65
9120.12.140 Compact scale Basic	No	0.2	6	Stainless steel	310 x 275	IP 65

## Products

Order number Variation	Approvable	Division g	Maximum load kg	Model substructure	Platform size mm	Protection class
9120.13.140 Compact scale Basic	No	0.5	15	Stainless steel	310 x 275	IP 65
9120.14.140 Compact scale Basic	No	1	32	Stainless steel	310 x 275	IP 65
9121.02.140 Compact scale Basic	No	0.2	6	Powder coated	400 x 300	IP 65
9121.03.140 Compact scale Basic	No	0.5	15	Powder coated	400 x 300	IP 65
9121.04.140 Compact scale Basic	No	1	32	Powder coated	400 x 300	IP 65
9121.05.140 Compact scale Basic	No	2	60	Powder coated	400 x 300	IP 65
9121.12.140 Compact scale Basic	No	0.2	6	Stainless steel	400 x 300	IP 65
9121.13.140 Compact scale Basic	No	0.5	15	Stainless steel	400 x 300	IP 65
9121.14.140 Compact scale Basic	No	1	32	Stainless steel	400 x 300	IP 65
9122.04.140 Compact scale Basic	No	1	32	Powder coated	520 x 400	IP 65
9122.05.140 Compact scale Basic	No	2	60	Powder coated	520 x 400	IP 65
9122.14.140 Compact scale Basic	No	1	32	Stainless steel	520 x 400	IP 65
9122.15.140 Compact scale Basic	No	2	60	Stainless steel	520 x 400	IP 65

## Accessories

Order number Variation		Description
2550.03.014		IT data cable for Basic and Standard 3 m, 9 pin, data cable for Professional 2 m, 5-9 pin (for not decoupled interface)
2564.20.005		Scale Connecting Plus, extensive software for transferring scale data to PC-based software (with activation code)
2557.25.002		UK power adapter
2563.21.004		RS 232 PC interface installed, 9 pin, (not decoupled, must be included in the purchase order, no retrofit possible)
2563.00.008		Keyboard wedge USB for RS232 scale interface to PC USB interface (for terminal professional data cable 2550.03.002 required)