



Baby scale Conformity assigned "Exklusiv"

7752

- ▶ Conformity assigned to class III, MPG class 1m
- ▶ Very fine division 2 g / 5 g
- ▶ Tara function: Covers / paddings can be tared
- ▶ Hold function: The weight value will freeze after stand still



Features

The Soehnle Professional Baby Scale 7752 is a two-part scale with high precision and reliability. The hold function guarantees a stable weight display even if the baby kicks on the scale. The scale is conformity rated according to Class III, MPG Class 1m and is therefore approved for use in doctors' surgeries and hospitals. A further advantage of the baby scale is its stable and tilt resistant stand for the safe weighing of your baby. Easy-care plastic and ergonomic shapes without grooves allow easy and hygienic cleaning.

- ▶ Attractive baby scale with very fine division of 2g / 5g
- ▶ 5- button operation with programmable function key
- ▶ Protection Class IP X2
- ▶ Backlit LCD Display, 16 mm digit height
- ▶ Manual input of tare values by function key
- ▶ Tara function: Covers / paddings can be tared
- ▶ Hold function: The weight value will freeze after stand still
- ▶ Provisional tare
- ▶ Simple differential weighing after breastfeeding / feeding possible (BMIF)
- ▶ Analogue and digital measurements with baby height rod, optionally available
- ▶ RS 232 interface (decoupled) optional
- ▶ Units in kg
- ▶ Mains operation

Products

| Order number | Approvable | Division | Maximum load | Platform size |
|--|------------|----------|--------------|-----------------|
| Variation | | g | kg | mm |
| 7752.01.001 Baby scale "Neo" | Yes | 2 5 | 6 15 | 601 x 385 x 129 |

Accessories

| Order number Variation | Description |
|----------------------------------|---|
| 2563.41.004 | Interface RS232, installed (must be included in the purchase order, no retrofit possible) |
| 2792.20.002 | Alibi memory, installed (must be included in the purchase order, no retrofit possible) |
| 2550.03.002 | Data cable PC/IT (Cable length 2 m) |
| 2550.00.008 | Data cable PC/IT (Cable length 2 – 10 m) |
| 2557.25.003 | UK adapter |